



### EXPANSION JOINT

Rubber

PTFE

Fabric

Inquiry

Order



Company: \_\_\_\_\_

Street: \_\_\_\_\_

Zip code: \_\_\_\_\_

City: \_\_\_\_\_

Contact: \_\_\_\_\_

e-mail: \_\_\_\_\_

Phone: \_\_\_\_\_

Project: \_\_\_\_\_











A

B

C

D

E



F

G

H

I

J

### Type | Description (colour): \_\_\_\_\_

Quantity: \_\_\_\_\_ piece      DN: \_\_\_\_\_      Face to face: \_\_\_\_\_ mm

Fluid: \_\_\_\_\_

Design pressure: \_\_\_\_\_ bar [overpressure]      Design temperature: \_\_\_\_\_ °C

Working pressure: \_\_\_\_\_ bar [overpressure]      Working temperature: \_\_\_\_\_ °C

Test pressure: \_\_\_\_\_ bar [overpressure]      max. temperature: \_\_\_\_\_ °C

Vacuum: \_\_\_\_\_ bar abs.      Flow rate: \_\_\_\_\_ m/s

Pressure surge: yes  / no       Overlay movements: \_\_\_\_\_

Axial extension: + \_\_\_\_\_ mm      Axial compression: \_\_\_\_\_ mm

Lateral: +/- \_\_\_\_\_ mm      angular: \_\_\_\_\_ mm

### Flange connection:

Flange standard / Nominal pressure: \_\_\_\_\_      Corrosion protection: \_\_\_\_\_

Special flange dimension:

Outside diameter: Ad \_\_\_\_\_ mm      Bolt circle diameter: Lk \_\_\_\_\_ mm

Number of holes: n \_\_\_\_\_ pcs.      Hole diameter: d2 \_\_\_\_\_ mm

Material: \_\_\_\_\_       Connection acc. to attached specifications

### Accessories:

Flame protec. cover \_\_\_\_\_       Sun protec. cover \_\_\_\_\_       Earth cover \_\_\_\_\_

Vakuu support. Ring \_\_\_\_\_       Deflector sleeve \_\_\_\_\_

### Certifications | Approvals | Regulations:

Approval test: \_\_\_\_\_ Pressure test: \_\_\_\_\_ Certificates: \_\_\_\_\_ Regulations: \_\_\_\_\_